



Model		TN-7580VM	TUE-7580VM	TUE-7580VM3 *	TUE-75120VM	TUE-75120VM3 *	TUE-75120M	TUE-75120M3 *
Electric Motor	H.P.	7.5	7.5		7.5		7.5	
	R.P.M / Frame	3450 / 184	1740 / 215		1740 / 215		1740 / 215	
	Volt./ Phase/ Amp.	208-230/ Single/ 33	208-230/ Single/ 33.3-31.3	208-230 or 460/ Three/ 19.8-17.9 or 8.97	208-230/ Single/ 33.3-31.3	208-230 or 460/ Three/ 19.8-17.9 or 8.97	208-230/ Single/ 33.3-31.3	208-230 or 460/ Three/ 19.8-17.9 or 8.97
Pump R.P.M		1161	1180		1180		1180	
Max. Working PSI.		175	175		175		175	
FAD-CFM	@ 90 PSI	22	23		23		23	
	@ 175 PSI	21	22		22		22	
TANK	Gal.	80	80		120		120	
	Style	Vertical	Vertical		Vertical		Horizontal	
	Code	ASME / CRN	ASME / CRN		ASME / CRN		ASME / CRN	
Weight (Lbs)		550	600	550	835	830	775	770
Magnetic Starter		Yes	Yes		Yes		Yes	
Outlet Ball Valve		1/2"	1/2"		1"		1"	
Ext. Manual Drain		1/4"	1/4"		1/4"		1/4"	
Premium Package		Option	Option		Option		Option	



Model		TUK-7580VM	TUK-7580VM3 *	TUK-75120VM	TUK-75120VM3 *	TUK-75120M	TUK-75120M3 *
Electric Motor	H.P.	7.5		7.5		7.5	
	R.P.M / Frame	1740 / 215		1740 / 215		1740 / 215	
	Volt./ Phase/ Amp.	208-230 / Single / 40	460 / Three / 8.97	208-230 / Single / 40	208-230 or 460 / Three / 19.8-17.9 or 8.97	208-230 / Single / 40	208-230 / Three / 19.8-17.9
Pump R.P.M		890		890		890	
Max. Working PSI.		175		175		175	
FAD-CFM	@ 90 PSI	24		24		24	
	@ 175 PSI	23		23		23	
TANK	Gal.	80		120		120	
	Style	Vertical		Vertical		Horizontal	
	Code	ASME / CRN		ASME / CRN		ASME / CRN	
Weight (Lbs)		620	610	950	945	955	950
Magnetic Starter		Yes		Yes		Yes	
Outlet Ball Valve		1/2"		1"		1"	
Ext. Manual Drain		1/4"		1/4"		1/4"	
Premium Package		Option		Option		Option	

* Three phase motor, customers must specify voltage (208-230 or 460 V) when ordering.

PUMA INDUSTRIES, INC.

1992 Airways Blvd. Memphis, TN 38114
 TEL:1-901-744-7979 FAX:1-901-744-7579

e-mail:sales@pumaaircenter.com
 http://www.pumaairusa.com

