

Oil Less Pumps

Single Stage Direct Drive Oil Less



Model	LA57	LA75	MG90
H.P.	3/4	3/4	1.5
R.P.M.	3450	1720	3450
* Displ. CFM	3.8	3.0	5.9
* Deliv. CFM	2.2	1.6	3.6
No. of Cyl.	1	1	1
Max. PSI.	140	140	140
Dimension (in)	11×7×10	13×9×10	12×6.3×5.7
Weight (lbs)	18	23	22
# dBA	76	75	78



Model	WS1	WD2	PF2	PF3
H.P.	1	2	1.5	3
R.P.M.	1720	1720	1720	1720
* Displ. CFM	3.8	7.6	6.1	10.4
* Deliv. CFM	2.0	4	3.5	5.8
No. of Cyl.	1	2	1	2
Max. PSI.	140	140	140	140
Dimension (in)	12×9×9	13×9×9	16×11×13	17×15×13
Weight (lbs)	22	31	44	61
# dBA	61	63	75	78

Single Stage Belt Drive Oil Less



Model	BF2	BUF5	BUF10
H.P.	2	5	10
R.P.M.	830	810	820
* Displ. CFM	9.7	24.7	47
* Deliv. CFM	6.7	18.5	31.5
No. of Cyl.	2	2	3
Max. PSI.	140	140	140
Dimension (in)	17×11×17	26×17×24	30×22×29
Weight (lbs)	50	125	210
Remarks		w/ Head unloader	w/ Head unloader

* Displacement CFM ratings are based on max. horsepower of units, and Delivered CFM ratings are measured at 90 PSIG under max. horsepower.
 # dBA may vary according to the configuration.

PUMA INDUSTRIES, INC.

1992 Airways Blvd. Memphis, TN 38114
 TEL:1-901-744-7979 FAX:1-901-744-7579

e-mail:sales@pumaaircenter.com
 http://www.pumaairusa.com

